



## Abrasive flap disc SLTflex (CER), mounting M14, 115 mm Ø, Grit: 40



### Order data

|              |               |
|--------------|---------------|
| Order number | 566312 40     |
| GTIN         | 4027497550579 |
| Item class   | 53L           |

### Description

#### Version:

The **sickle-shaped strips** (patented) are radially linked to a high-strength GRP centre. The **pad-less design** permits an **extremely large overlap between strips**. Very high coating density. M14 threaded mounting, **no clamping nut required**.

**Ceramic grit (CER)** with active upper layer bonding for **heavy duty**.

#### Application:

For use in **inaccessible places**, contour grinding and for **grinding out of weld fillets**. Large overlap between strips permits **soft cutting**.

maximum circumferential speed: 80 m/s

Shape description: dished with overlap between strips

### Technical description

|                      |                                    |
|----------------------|------------------------------------|
| Shape description    | dished with overlap between strips |
| Grit                 | 40                                 |
| Disc Ø               | 115 mm                             |
| Grinding medium code | Ceramic                            |

|   |                    |
|---|--------------------|
| Iron, sulphur and chlorine constituents | <0.1 %             |
| Product name attribute                  | 115 mm Ø           |
| Thread                                  | M14                |
| optimised for material                  | INOX               |
| maximum circumferential speed           | 80 m/s             |
| Type of product                         | Abrasive flap disc |