



Abrasive flap disc for stainless steel, POLIFAN-CURVE (CER), Disc Ø×Width: 115X14 mm



Order data

Order number	566325 115X14
GTIN	4007220827444
Item class	55P

Description

Version:

Flap disc for highly demanding grinding of fillet welds. The **radial design with special arrangement of the segments** enables optimum application of the abrasive material on the radius. High metal removal rate, service life, and shape stability.

SGP CURVE STEELOX (CER) in 60 grit for fine surfaces and cool grinding on materials with poor thermal conductivity.

Application:

Precise grinding out of weld fillet geometries, chamfering, deburring. Medium width version (M) for fillet welds > 5 mm.

maximum circumferential speed: 80 m/s

Shape description: radial

Bore Ø: 22.23 mm

Width at radius: 11 mm

for weld fillet radii: > 5 mm

Technical description

Disc thickness	14 mm
----------------	-------

Grit	60
Shape description	radial
for weld fillet radii	> 5 mm
Bore Ø	22.23 mm
Width at radius	11 mm
Disc Ø	115 mm
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Abrasive flap disc