



## Abrasive flap disc for stainless steel, POLIFAN-CURVE (CER), Disc Ø×Width: 115X16 mm



### Order data

Order number	566325 115X16
GTIN	4007220827451
Item class	55P

### Description

#### Version:

Flap disc for highly demanding grinding of fillet welds. The **radial design with special arrangement of the segments** enables optimum application of the abrasive material on the radius. High metal removal rate, service life, and shape stability.

**SGP CURVE STEELOX (CER)** in 60 grit for fine surfaces and cool grinding on materials with poor thermal conductivity.

#### Application:

**Precise grinding out of weld fillet geometries**, chamfering, deburring. Wide version (L) for fillet welds > 8 mm.

maximum circumferential speed: 80 m/s

Shape description: radial

Bore Ø: 22.23 mm

Width at radius: 14 mm

for weld fillet radii: > 8 mm

### Technical description

Disc thickness	16 mm
----------------	-------

Width at radius	14 mm
Bore Ø	22.23 mm
Shape description	radial
Grit	60
for weld fillet radii	> 8 mm
Disc Ø	115 mm
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
optimised for material	INOX
maximum circumferential speed	80 m/s
Type of product	Abrasive flap disc