



Fibre disc Aluminium Oxide (A), Ø 115 mm, Grit: 120



Order data

Order number	566410 120
GTIN	4045197527042
Item class	52M

Description

Version:

Tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots.
HOLEX universal fibre disc for grinding all metals. Grit type: **Aluminium oxide (A)**.

Application:

Limited to maximum 80 m/s circumferential speed with backing pads No. 566650 / 566670 on angle grinders. For **grinding flat and curved surfaces** with a high degree of **flexibility**.
 maximum circumferential speed: 80 m/s

Technical description

Grit	120
Disc Ø	115 mm
Grinding media	Regular aluminium oxide (A)
Grinding medium code	A
Grinding media backing	Vulcanised fibre
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 115 mm

Adapter	Roloc™ quick-change system
Bore Ø	22.23 mm
suitable for quick-change system	Roloc™
optimised for material	Steel
maximum circumferential speed	80 m/s
maximum speed	13300 rpm
Type of product	Fibre disc

Accessories

Backing pad hard/ribbed External Ø 115 mm	566672 115
ISO backing pad flexible/smooth External Ø 108 mm	566650 108
ISO backing pad medium hard/rippled External Ø 108 mm	566670 108