


ZF 714 fibre disc zirconium aluminium oxide (ZA), Ø 115 mm, Grit: 60

Order data

| | |
|--------------|---------------|
| Order number | 566430 60 |
| GTIN | 4018875526118 |
| Item class | 56V |

Description
Version:

Tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots. **VSM ZF 714 fibre disc** with **high cutting performance** and long working life. Cool grinding. Especially for alloy steels, non-ferrous metals, and grey cast iron.

Grit type: **Zirconium Aluminium Oxide (ZA) active coated**.

Application:

Limited to maximum 80 m/s circumferential speed with backing pads No. 566650 / 6670 on angle grinders. For **grinding flat and curved surfaces** with a high degree of **flexibility**. maximum circumferential speed: 80 m/s

Technical description

| | |
|---|--------------------------------|
| Grit | 60 |
| Disc Ø | 115 mm |
| Grinding media | Zirconium aluminium oxide (ZA) |
| Grinding medium code | ZA |
| Grinding media backing | Fibre disc |
| Iron, sulphur and chlorine constituents | < 0.1 % |

| | |
|-------------------------------|------------|
| Product name attribute | Ø 115 mm |
| Bore Ø | 22.23 mm |
| optimised for material | Steel |
| optimised for material | INOX |
| maximum circumferential speed | 80 m/s |
| maximum speed | 13300 rpm |
| Type of product | Fibre disc |

Accessories

| | |
|--|------------|
| ISO backing pad medium hard/ripped External Ø 108 mm | 566670 108 |
| Backing pad hard/ribbed External Ø 115 mm | 566672 115 |
| ISO backing pad flexible/smooth External Ø 108 mm | 566650 108 |