

**Fibre disc (CER) 787C, Ø 115 mm, Grit: 60****Order data**

Order number	566477 60
GTIN	50076308897340
Item class	53F

Description**Version:**

The grinding aid is an additive which ensures cool grinding without discolouration and reduces the need to add lubricants.

The precisely formed **high-performance abrasive grit** in 3M™ products consists of defined ceramic triangles optimally arranged on the grinding surface. **Greatly increased removal rate** with very long working life and even finish.

Extremely tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots.

High-performance fibre disc with open distribution.

Application:

For the machining of **stainless steel, aluminium**, titanium and nickel alloys.

Limited to maximum 80 m/s circumferential speed with backing pads No. 566690 / 566692 on angle grinders. The quick-cutting abrasive grit permits **comfortable and ergonomic working** without the need to exert great pressure. At the same time, the high removal rate of 3M™ fibre discs makes them a real alternative to roughing discs and flap discs.

maximum circumferential speed: 80 m/s

Technical description

Grinding media	Ceramic grit
Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 115 mm
Bore Ø	22.23 mm
optimised for material	INOX
optimised for material	Aluminium
maximum circumferential speed	80 m/s
Type of product	Fibre disc