




Fibre disc Aluminium Oxide (A), Ø 125 mm, Grit: 24



Order data

| | |
|--------------|---------------|
| Order number | 566510 24 |
| GTIN | 4045197287595 |
| Item class | 52M |

Description

Version:

Tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots.
HOLEX universal fibre disc for grinding all metals. Grit type: **Aluminium oxide (A)**.

Application:

Limited to maximum 80 m/s circumferential speed with backing pads No. 566650 / 566670 on angle grinders. For **grinding flat and curved surfaces** with a high degree of **flexibility**.
 maximum circumferential speed: 80 m/s

Technical description

| | |
|---|-----------------------------|
| Grit | 24 |
| Disc Ø | 125 mm |
| Grinding media | Regular aluminium oxide (A) |
| Grinding medium code | A |
| Grinding media backing | Vulcanised fibre |
| Iron, sulphur and chlorine constituents | < 0.1 % |
| Product name attribute | Ø 125 mm |

| | |
|----------------------------------|----------------------------|
| Adapter | Roloc™ quick-change system |
| Bore Ø | 22.23 mm |
| suitable for quick-change system | Roloc™ |
| optimised for material | Steel |
| maximum circumferential speed | 80 m/s |
| maximum speed | 12200 rpm |
| Type of product | Fibre disc |

Accessories

| | |
|--|------------|
| ISO backing pad medium hard/ripped External Ø 117 mm | 566670 117 |
| Backing pad hard/ribbed External Ø 125 mm | 566672 125 |
| ISO backing pad flexible/smooth External Ø 117 mm | 566650 117 |