




## Fibre disc Aluminium Oxide (A), Ø 125 mm, Grit: 60



### Order data

Order number	566510 60
GTIN	4045197292018
Item class	52M

### Description

#### Version:

Tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots.  
**HOLEX universal fibre disc** for grinding all metals. Grit type: **Aluminium oxide (A)**.

#### Application:

Limited to maximum 80 m/s circumferential speed with backing pads No. 566650 / 566670 on angle grinders. For **grinding flat and curved surfaces** with a high degree of **flexibility**.  
 maximum circumferential speed: 80 m/s

### Technical description

Grit	60
Disc Ø	125 mm
Grinding media	Regular aluminium oxide (A)
Grinding medium code	A
Grinding media backing	Vulcanised fibre
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 125 mm

Adapter	Roloc™ quick-change system
Bore Ø	22.23 mm
suitable for quick-change system	Roloc™
optimised for material	Steel
maximum circumferential speed	80 m/s
maximum speed	12200 rpm
Type of product	Fibre disc

---

## Accessories

ISO backing pad medium hard/ripped External Ø 117 mm	566670 117
Backing pad hard/ribbed External Ø 125 mm	566672 125
ISO backing pad flexible/smooth External Ø 117 mm	566650 117