


XF 850 fibre disc (CER), Ø 125 mm, Grit: 40

Order data

Order number	566556 40
GTIN	4018875669761
Item class	56V

Description
Version:

Tear-resistant but very flexible **vulcanised fibre**. Bore diameter 22.23 mm and crossed slots. **VSM XF 850 universal fibre disc** with **high and aggressive cutting performance** and long working life. Cool grinding. Ideal for working alloy steels and aluminium alloys.

Grit type: **Ceramic Zirconium Aluminium Oxide mixed grit with cooling, active coating(TOP SIZE)**.

Application:

Limited to maximum 80 m/s circumferential speed with backing pads No. 566650 / 6670 on angle grinders. For **grinding flat and curved surfaces** with a high degree of **flexibility**. maximum circumferential speed: 80 m/s

Technical description

Grit	40
Disc Ø	125 mm
Grinding media	Ceramic Zirconium Aluminium Oxide mixed grit with cooling, active coating (TOP SIZE).

Grinding medium code	Ceramic
Grinding media backing	Fibre disc
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 125 mm
Bore Ø	22.23 mm
optimised for material	Aluminium
optimised for material	INOX
maximum circumferential speed	80 m/s
maximum speed	12200 rpm
Type of product	Fibre disc

Accessories

ISO backing pad flexible/smooth External Ø 117 mm	566650 117
ISO backing pad medium hard/ripped External Ø 117 mm	566670 117
Backing pad hard/ribbed External Ø 125 mm	566672 125