

3M**Coarse cleaning disc (SiC), XT-RD PRO, Disc Ø: 115 mm****Order data**

Order number	566726 115
GTIN	4054596605725
Item class	53M

Description**Version:**

Cleaning discs with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad.

Very **coarse non-woven abrasive mesh structure**, will not clog even when used on soft thick coatings.

Extremely hard and aggressive fleece body creates a coarse finish with a very high cleaning effectiveness. Very **long working life, even when used on edges**.

Application:

For rust removal, paint removal, dressing weld seams and removing surface dirt.

With **glass fibre backing pad for direct clamping** on angle grinders.

Note:

For deburring wheels for double-ended bench grinding machines, see No. 556270 onwards.

maximum circumferential speed: 60 m/s

Grit designation: very coarse

Bore Ø: 22.23 mm

Bore Ø: 22.23 mm

recommended speed: 5000 - 7000 rpm

maximum speed: 11000 rpm

Technical description

recommended speed	5000 - 7000 rpm
Bore Ø	22.23 mm
Disc Ø	115 mm
maximum speed	11000 rpm
Grinding medium code	SiC
Degree of hardness	very hard
Grit designation	very coarse
Iron, sulphur and chlorine constituents	< 0.1 %
Shape description	flat
Product name attribute	XT-RD PRO
maximum circumferential speed	60 m/s
Type of product	Rough cleaning non-woven abrasive mesh