STARCKE®

Paper velour-backed abrasive disc (A), Ø 115 mm, Grit: 180



Order data

Order number	567705 180
GTIN	4002748776878
Item class	56Z

Description

Version:

Abrasive paper thickness 540 FK (F paper, 40 to 180 grit) to paper thickness 544 C3K (240 – 400 grit, stearate coated) with **high strength and dense distribution.**

High removal rates due to specially treated abrasive grit (A).

The back of the disc is covered with velour loops which are self-attaching to hook and loop fastener backing pads, e.g. No. 567760. For quick disc changing.

Application:

On **angle grinders** / eccentric grinders with hook and loop fastener pads (dust removal not available). Maximum working speed **40 m/s.**

General purpose for grinding metal, non-ferrous metals, varnish, paint, wood, and plastic. **Note:**

Suitable hand sanding block for hook and loop grinding discs see No. 567857 size 125 and Gr.150. See No. 566902 – 566950 for velour abrasive discs. For mini grinding systems \emptyset 50 mm and \emptyset 75 mm, see No. 554005 onwards.

maximum circumferential speed: 40 m/s

Technical description

Grit

180

Disc Ø	115 mm
Manufacturer's designation	540 FK
Grinding medium code	А
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 115 mm
Propulsive equipment	Angle grinder
maximum circumferential speed	40 m/s
Type of product	Velour-backed abrasive disc

Accessories

Hook and loop polishing pad, M14 External Ø 115 mm	567762 115
Hook and loop backing pad, M14 External Ø 115 mm	567760 115