STARCKE®

Paper velour-backed abrasive disc (A), Ø 125 mm, Grit: 120



Order data

Order number	567715 120
GTIN	4002748776922
Item class	56Z

Description

Version:

Abrasive paper thickness 540 FK (F paper, 40 to 180 grit) to thickness 544 C3K (240 – 400 grit, stearate coated) with **high strength and dense distribution.** High removal rates due to specially treated abrasive grit **(A).**

The back of the disc is covered with velour loops which are self-attaching to hook and loop fastener backing pads, e.g. No. 567760 . For quick disc changing.

Application:

On **angle grinders** / eccentric grinders with hook and loop fastener pads (dust removal not available). Maximum working speed **40 m/s.**

General purpose for grinding metal, non-ferrous metals, varnish, paint, wood, and plastic. **Note:**

Suitable hand sanding block for hook and loop grinding discs see No. 567857 size 125 and Gr.150. See No. 566902 – 566950 for velour abrasive discs. For mini grinding systems \varnothing 50 mm and \varnothing 75 mm, see No. 554005 onwards.

maximum circumferential speed: 40 m/s

Technical description

Grit	120
------	-----



Disc Ø	125 mm
Manufacturer's designation	540 FK
Grinding medium code	Α
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 125 mm
Propulsive equipment	Angle grinder
maximum circumferential speed	40 m/s
Type of product	Velour-backed abrasive disc

Accessories

Hook and loop polishing pad, M14 External Ø 125 mm	567762 125
Hand sanding block with hook and loop fastening suitable for disc Ø 125 mm	567857 125
Hook and loop backing pad, M14 External Ø 125 mm	567760 125