

STARCKE®**Paper velour-backed abrasive disc (A), Ø 150 mm, Grit: 120****Order data**

Order number	567725 120
GTIN	4002748776564
Item class	56Z

Description**Version:**

Abrasive thickness 540 FK (F paper, 40 to 180 grit) to thickness 544 C3K (240 – 400 grit, stearate coated) with **high strength and dense distribution**. High removal rates due to specially treated abrasive grit (**A**).

The **back of the disc is covered with velour loops** which are self-attaching to **hook and loop fastener backing pads**, e.g. No. **567760** . For quick disc changing.

Application:

On **angle grinders** / eccentric grinders with hook and loop fastener pads (dust removal not available). Maximum working speed **40 m/s**.

General purpose for grinding metal, non-ferrous metals, varnish, paint, wood, and plastic.

Note:

Suitable hand sanding block for hook and loop grinding discs see No. 567857 size 125 and Gr.150. See No. 566902 – 566950 for velour abrasive discs. For mini grinding systems Ø 50 mm and Ø 75 mm, see No. 554005 onwards.

maximum circumferential speed: 40 m/s

Technical description

Grit	120
------	-----

Disc Ø	150 mm
Manufacturer's designation	540 FK
Grinding medium code	A
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 150 mm
Propulsive equipment	Angle grinder
maximum circumferential speed	40 m/s
Type of product	Velour-backed abrasive disc

Accessories

Hand sanding block with hook and loop fastening suitable for disc Ø 150 mm	567857 150
Hook and loop backing pad, M14 External Ø 150 mm	567760 150
Hook and loop polishing pad, M14 External Ø 150 mm	567762 150