


STARCKE®
Paper velour-backed abrasive disc (A) 8 + 1 holes, Ø 150 mm, Grit: 320

Order data

Order number	567755 320
GTIN	4002748765353
Item class	56Z

Description
Version:

Abrasive paper thickness 540 FK (F-paper, 40 to 180 grit) or thickness 544 C3K (240 – 800 grit, stearate coated) with **high strength and dense distribution**.

High material removal rates due to specially treated abrasive grit **(A)**.

The **back of the disc is covered with velour loops which automatically cling on** allowing quick disc change.

With 9-hole perforation for Festo RO 1E/RO 2E/WET 2E, Makita BO6030, Bosch GX 150 with dust extraction.

Application:

General purpose for grinding metal, non-ferrous metals, varnish, paint, wood, and plastic.

On **orbital sanders** with hook and loop pads e.g. No. 567885 / 567990. Maximum circumferential speed **40 m/s**.

maximum circumferential speed: 40 m/s

Technical description

Grit	320
Disc Ø	150 mm

Grinding medium code	A
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 150 mm
Number of dust extraction holes	9
Propulsive equipment	Orbital sander
maximum circumferential speed	40 m/s
Type of product	Velour-backed abrasive disc

Accessories

PU backing pad External Ø 150 mm	567885 150
Multi-hole PU backing pad Outer Ø 150 mm	567887 150
Multi-hole PU backing pad External Ø 147 mm	567990 147