

LESSMANN®
THE GERMAN BRUSH COMPANY
**Wire wheel brush Steel wire 0.30 / 0.35 mm, Brush Ø D1× bristle width L1:
 250X30 mm**

Order data

Order number	570100 250X30
GTIN	4017359079966
Item class	57L

Description
Version:

Waved wire firmly crimped into the steel body. **High density**, high concentricity, and good wear resistance. Adaptable to various different mounting bores by use of **interchangeable reducing rings** (supplied). Bore with double spline.

Application:

Use on bench grinder or polishing machines, or on machines with flexible drive heads. For roughening, cleaning, removing rust, and scale etc.

Brush width: 25 mm

Bore Ø d₁: 50.8 mm

Bore Ø can be opened up to: 80 mm

Reducing ring Ø: 12/12.7/16/20/22.2/25.4/30 mm

Length of brush section H₁: 50 mm

maximum speed: 3600 rpm

Technical description

Reducing ring Ø	12/12.7/16/20/22.2/25.4/30 mm
Length of brush section H ₁	50 mm

Bore \varnothing can be opened up to	80 mm
Brush \varnothing D ₁	250 mm
maximum speed	3600 rpm
Brush width	25 mm
Bore \varnothing d ₁	50.8 mm
Type of product	Wheel brush