

**LESSMANN®**  
THE GERMAN BRUSH COMPANY
**Wire wheel brush Steel wire 0.20 mm, Brush Ø D1× bristle width L1: 150X22 mm**

**Order data**

Order number	570150 150X22
GTIN	4017359032367
Item class	57L

**Description**
**Version:**

Waved wire firmly crimped into the steel body. **High density**, high concentricity, and good wear resistance. Adaptable to various different mounting bores by use of **interchangeable reducing rings** (supplied).

**Application:**

Use on bench grinder or polishing machines, or on machines with flexible drive heads.

For roughening, cleaning, removing rust, and scale etc.

Brush width: 20 mm

Bore Ø d<sub>1</sub>: 40 mm

Reducing ring Ø: 12.7 / 16 / 20 / 22.2 / 25.4 / 32 mm

Length of brush section H<sub>1</sub>: 33 mm

maximum speed: 6000 rpm

**Technical description**

Reducing ring Ø	12.7 / 16 / 20 / 22.2 / 25.4 / 32 mm
Length of brush section H <sub>1</sub>	33 mm

Brush $\varnothing D_1$	150 mm
Brush width	20 mm
maximum speed	6000 rpm
Bore $\varnothing d_1$	40 mm
Type of product	Wheel brush