### LESSMANN®

Wheel brush Steel wire 0.50 mm, Brush Ø D1× bore Ø d1 / thread M: 125XM14 mm



## **Order data**

Order number	571200 125XM14
GTIN	4017359024805
Item class	57L

## Description

#### Version:

Straight round brush with smooth wire 0.50 mm, **plaited** and firmly crimped into the steel body. **Very aggressive brushing effect with high wear resistance.** 

#### Application:

Left-hand plaited, reliably avoids premature unwinding.

For heavy brush work, e.g. descaling, removing rust, removing paint, roughening, cleaning metal parts, also for cleaning formwork boards. With **internal thread M14**, for direct mounting **on angle grinders**.

# Thread M: M14

Bristle width L<sub>1</sub>: 14 mm Length of brush section H<sub>1</sub>: 29 mm Number of twisted knots: 20 maximum speed: 12500 rpm

# **Technical description**

Length of brush section H<sub>1</sub>

29 mm

Brush $\emptyset$ D <sub>1</sub>	125 mm
maximum speed	12500 rpm
Bristle thickness	0.5 mm
Number of twisted knots	20
Bristle width L <sub>1</sub>	14 mm
Thread M	M14
Brush material	Steel wire
Twisted knotting	left-hand plait
Type of product	Wheel brush