## **LESSM**NN°

# Wheel brush Steel wire 0.50 mm, Brush Ø D1 $\times$ bore Ø d1 / thread M: 178XM14 mm



#### **Order data**

Order number	571200 178XM14
GTIN	4017359016923
Item class	57L

## **Description**

#### **Version:**

Straight round brush with smooth wire 0.50 mm, **plaited** and firmly crimped into the steel body. **Very aggressive brushing effect with high wear resistance.** 

#### **Application:**

Left-hand plaited, reliably avoids premature unwinding.

For heavy brush work, e.g. descaling, removing rust, removing paint, roughening, cleaning metal parts, also for cleaning formwork boards. With **internal thread M14**, for direct mounting **on angle grinders**.

Thread M: M14

Bristle width L<sub>1</sub>: 14 mm

Length of brush section H₁: 38 mm

Number of twisted knots: 32 maximum speed: 12500 rpm

## **Technical description**

maximum speed	12500 rpm
---------------	-----------

Bristle thickness	0.5 mm
Number of twisted knots	32
Length of brush section H <sub>1</sub>	38 mm
Brush Ø D₁	178 mm
Bristle width L <sub>1</sub>	14 mm
Thread M	M14
Brush material	Steel wire
Twisted knotting	left-hand plait
Type of product	Wheel brush