LESSMNN°

Wheel brush Steel wire 0.50 mm, Brush Ø D1× bore Ø d1 / thread M: 200X22 mm



Order data

| Order number | 571200 200X22 |
|--------------|---------------|
| GTIN | 4017359013779 |
| Item class | 57L |

Description

Version:

Straight round brush with smooth wire 0.50 mm, **plaited** and firmly crimped into the steel body. **Very aggressive brushing effect with high wear resistance.**

Application:

Left-hand plaited, reliably avoids premature unwinding.

For heavy brush work, e.g. descaling, removing rust, removing paint, roughening, cleaning metal parts, also for cleaning formwork boards.

Bristle width L₁: 14 mm

Length of brush section H₁: 41 mm

Number of twisted knots: 36 maximum speed: 9000 rpm

Technical description

| Brush Ø D ₁ | 200 mm |
|------------------------|----------|
| Bristle thickness | 0.5 mm |
| maximum speed | 9000 rpm |

| Length of brush section H ₁ | 41 mm |
|--|-----------------|
| Number of twisted knots | 36 |
| Bristle width L ₁ | 14 mm |
| Bore Ø d ₁ | 22 mm |
| Brush material | Steel wire |
| Twisted knotting | left-hand plait |
| Type of product | Wheel brush |