Interior brush NOVOFLEX-B SiC120 grit, Type: 22



Order data

| Order number | 574490 22 |
|--------------|---------------|
| GTIN | 4013349529084 |
| Item class | 57L |

Description

Version:

Self-centring interior brush with flexible bristles carrying **silicon carbide spheres.** Overall length 200 mm.

Application:

For **chamfering**, **finishing of surfaces** and **honing**. Generates **fine evenly ground surface** with high contact area. For use in power drills and fixed drills. Recommended speed 350 – 700 rpm, contact time 20 – 40 seconds.

Note:

Do not use dry, use with cutting oil No. 084205. Grinding medium code: SiC Brush \emptyset D₁: 25 mm Shank \emptyset D₅: 4.6 mm Working length L₃: 70 mm suitable for bore \emptyset : 20.1 - 22 mm

Technical description

| suitable for bore Ø | 20.1 - 22 mm |
|------------------------|-----------------|
| Working length L₃ | 70 mm |
| Brush Ø D ₁ | 25 mm |
| Shank Ø D _s | 4.6 mm |
| Brush material | Silicon carbide |
| Grinding medium code | SiC |
| Grit | 120 |

| recommended speed | 350 - 700 rpm |
|---|----------------|
| Type of product | Internal brush |
| | |
| Accessories | |
| High-performance cutting oil free of mineral oil UV 80 Contents 0,25 l | 084205 0,25 |
| High-performance cutting oil free of mineral oil UV 80 Contents 20 l | 084205 20 |
| High-performance cutting oil free of mineral oil UV 80 Contents 5 l | 084205 5 |