Interior brush NOVOFLEX-B SiC120 grit, Type: 29



Order data

Order number	574490 29
GTIN	4013349528193
Item class	57L

Description

Version:

Self-centring interior brush with flexible bristles carrying **silicon carbide spheres.** Overall length 200 mm.

Application:

For **chamfering, finishing of surfaces** and **honing.** Generates **fine evenly ground surface** with high contact area. For use in power drills and fixed drills. Recommended speed 350 – 700 rpm, contact time 20 – 40 seconds.

Note:

Do not use dry, use with cutting oil No. 084205.

Grinding medium code: SiC

Brush Ø D₁: 32 mm Shank Ø D₅: 5.1 mm

Working length L₃: 70 mm

suitable for bore Ø: 27.1 - 29 mm

Technical description

suitable for bore \varnothing	27.1 - 29 mm
Brush Ø D₁	32 mm
Working length L₃	70 mm
Shank Ø D _s	5.1 mm
Brush material	Silicon carbide
Grinding medium code	SiC
Grit	120

recommended speed	350 - 700 rpm
Type of product	Internal brush
Accessories	
High-performance cutting oil free of mineral oil LIV 80	
Contents 0,25 l	084205 0,25
High performance cutting oil free of mineral oil LIV 90	
Contents 20 l	084205 20
Contents 5 l	084205 5
High-performance cutting oil free of mineral oil UV 80 Contents 20 l High-performance cutting oil free of mineral oil UV 80	084205 20