# Interior brush NOVOFLEX-B SiC120 grit, Type: 32



### **Order data**

| Order number | 574490 32     |
|--------------|---------------|
| GTIN         | 4013349529145 |
| Item class   | 57L           |

## **Description**

#### **Version:**

Self-centring interior brush with flexible bristles carrying **silicon carbide spheres.** Overall length 200 mm.

### **Application:**

For **chamfering, finishing of surfaces** and **honing.** Generates **fine evenly ground surface** with high contact area. For use in power drills and fixed drills. Recommended speed 350 – 700 rpm, contact time 20 – 40 seconds.

#### Note:

Do not use dry, use with cutting oil No. 084205.

Grinding medium code: SiC

Brush Ø D<sub>1</sub>: 35 mm Shank Ø D<sub>s</sub>: 5.7 mm

Working length L₃: 70 mm

suitable for bore Ø: 29.1 - 32 mm

## **Technical description**

| Brush Ø D₁             | 35 mm           |
|------------------------|-----------------|
| suitable for bore Ø    | 29.1 - 32 mm    |
| Working length L₃      | 70 mm           |
| Shank Ø D <sub>s</sub> | 5.7 mm          |
| Brush material         | Silicon carbide |
| Grinding medium code   | SiC             |
| Grit                   | 120             |

| recommended speed  | 350 - 700 rpm  |
|--|----------------|
| Type of product  | Internal brush |
|  |                |
| Accessories  |                |
| High-performance cutting oil free of mineral oil LIV 80  |                |
| Contents 0,25 l  | 084205 0,25    |
| High performance cutting oil free of mineral oil LIV 90  |                |
| Contents 20 l  | 084205 20      |
|  |                |
| Contents 5 l   | 084205 5       |
| High-performance cutting oil free of mineral oil UV 80 Contents 20 l  High-performance cutting oil free of mineral oil UV 80 | 084205 20      |