

**LESSMANN®**  
THE GERMAN BRUSH COMPANY

## Plaited end brush Stainless steel wire, Brush Ø D1× bristle thickness: 28X0,35 mm



### Order data

Order number	574900 28X0,35
GTIN	4017359039427
Item class	57L

### Description

#### Version:

Smooth hardened wire, crimped into steel ferrule, **shank Ø 6 mm**, even density, extremely wear-resistant.

Stainless wire quality 1.4401 (AISI 316). Carrier body with plastic sheathing for machining stainless steel.

#### Application:

For deburring, removing paint, and for all moderate to heavy brushing jobs. **As speed increases the brush opens, this allows it to be introduced even into tight spaces**, e.g. when brushing the inside of casings.

Brush Ø D<sub>1</sub>: 28 mm

Length of brush section H<sub>1</sub>: 28 mm

Number of twisted knots: 12

maximum speed: 20000 rpm

### Technical description

Bristle thickness	0.35 mm
Number of twisted knots	12
Length of brush section H <sub>1</sub>	28 mm
maximum speed	20000 rpm
Brush Ø D <sub>1</sub>	28 mm

Shank $\varnothing D_s$	6 mm
Brush material	Stainless steel wire
Twisted knotting	left-hand plait
Type of product	End brush