### LESSMANN®

Plaited end brush Stainless steel wire, Brush Ø D1× bristle thickness: 28X0,50 mm



### Order data

Order number	574900 28X0,50
GTIN	4017359045763
Item class	57L

## Description

#### Version:

Smooth hardened wire, crimped into steel ferrule, **shank Ø 6 mm**, even density, extremely wear-resistant.

Stainless wire quality 1.4401 (AISI 316). Carrier body with plastic sheathing for machining stainless steel.

#### Application:

For deburring, removing paint, and for all moderate to heavy brushing jobs. As speed increases the brush opens, this allows it to be introduced even into tight spaces, e.g. when brushing the inside of casings.

Brush  $\emptyset$  D<sub>1</sub>: 28 mm Length of brush section H<sub>1</sub>: 28 mm Number of twisted knots: 12 maximum speed: 20000 rpm

# **Technical description**

maximum speed	20000 rpm
Length of brush section H <sub>1</sub>	28 mm
Bristle thickness	0.5 mm
Brush Ø D <sub>1</sub>	28 mm
Number of twisted knots	12

© Hoffmann GmbH Qualitätswerkzeuge

Shank Ø D <sub>s</sub>	6 mm
Brush material	Stainless steel wire
Twisted knotting	left-hand plait
Type of product	End brush