# Garant

Disc brush with shank, ceramic grit (CER), Ø 50 mm, Grit: 80



## Order data

Order number	575026 80
GTIN	4062406287054
Item class	51P

### Description

#### Version:

Disc brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life.

6 mm shank, solidly cast in place.

Nylon bristles with ceramic grit content. More aggressive abrasive effect.

#### Advantage:

- · Workpiece post-processing directly after the machining process.
- Reproducible results due to continuous exposure of the abrasive grit.
- Process reliability thanks to high stability and accuracy of the shape.
- Quick and secure mounting without further accessories.
- · Very high concentricity.

### **Application:**

On **CNC machining centres** and when used by **robots**, preferably **wet grinding** with cooling lubricant. Machining of flat components: precise **deburring**, **edge rounding**, **finish machining** after milling, **surface finishing** e.g. of sealing and mating faces.

#### Note:

Special versions available on request. Grinding medium code: Ceramic Bristle length L<sub>3</sub>: 25 mm Shank  $\emptyset$  D<sub>s</sub>: 6 mm Grit designation: coarse Bristle thickness: 1.2 mm

# **Technical description**

Bristle thickness	1.2 mm
Feed	800 - 3000 mm/min
Grit designation	coarse
Infeed	0.3 (fine) – 2.0 (coarse) mm
Grit	80
Shank Ø D <sub>s</sub>	6 mm
Product name attribute	Ø 50 mm
Brush Ø D <sub>1</sub>	50 mm
Disc dia. D <sub>2</sub>	55 mm
Grinding media	Ceramic grit (CER)
Grinding medium code	Ceramic
Bristle length L <sub>3</sub>	25 mm
recommended speed	1200 - 2400 rpm
maximum speed	4500 rpm
Type of product	Disc brush