

Disc brush, ceramic grit (CER), Ø 119 mm, Grit: 80



Order data

Order number	575035 80
GTIN	4045197892768
Item class	51P

Description

Version:

With longitudinal groove for clamping on face mill arbors (DIN 6357) and combination face mill adapters (DIN 6358).

Disc brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life.

Nylon bristles with **ceramic grit content.** More aggressive abrasive effect.

Advantage:

- · Workpiece rework directly after the machining process.
- · Reproducible results due to constantly exposed grinding grit.
- · Good process reliability thanks to high shape stability and shape accuracy.
- · Quick and secure installation without further accessories.
- · Very low radial run-out.

Application:

On **CNC** machining centres and when used by robots, preferably wet grinding with cooling lubricant. Machining of flat components: precise **deburring**, **edge rounding**, **finish machining** after milling, **surface finishing** e.g. of sealing and mating faces.

Note:

Special versions available on request.

Grinding medium code: Ceramic

Bore \emptyset d₁: 27 with groove mm

Grit designation: coarse Bristle thickness: 1.2 mm

Technical description

Bristle thickness	1.2 mm		
Distie trickiess	1.2 111111		
Grit designation	coarse		
Grit	80		
Feed	3500 - 6500 mm/min		
Infeed	0.8 (fine) – 1.5 (coarse) mm		
Product name attribute	Ø 119 mm		
Brush Ø D₁	119 mm		
Disc dia. D ₂	125 mm		
Grinding media	Ceramic grit (CER)		
Grinding medium code	Ceramic		
Bristle length L₃	38 mm		
Working area ∅	119 mm		
Bore Ø d ₁	27 with groove mm		
recommended speed	1100 - 1400 rpm		
maximum speed	3000 rpm		
Type of product	Disc brush		

Accessories

Tightening screw with internal	cooling 1	for mandre	el Ø 27
mm			

575096 27