

Garant**Disc brush, ceramic grit (CER), Ø 144 mm, Grit: 80****Order data**

Order number	575038 80
GTIN	4045197892782
Item class	51P

Description**Version:**

With longitudinal groove for clamping on face mill arbors (DIN 6357) and combination face mill adapters (DIN 6358).

Disc brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life.

Nylon bristles with **ceramic grit content**. More aggressive abrasive effect.

Advantage:

- **Workpiece rework directly after the machining process.**
- **Reproducible results due to constantly exposed grinding grit.**
- **Good process reliability thanks to high shape stability and shape accuracy.**
- **Quick and secure installation without further accessories.**
- **Very low radial run-out.**

Application:

On **CNC machining centres** and when used by **robots**, preferably **wet grinding** with cooling lubricant. Machining of flat components: precise **deburring**, **edge rounding**, **finish machining** after milling, **surface finishing** e.g. of sealing and mating faces.

Note:

Special versions available on request.

Grinding medium code: Ceramic

Bore $\varnothing d_1$: 32 with groove mm

Grit designation: coarse

Bristle thickness: 1.2 mm

Technical description

Grit designation	coarse
Grit	80
Bristle thickness	1.2 mm
Infeed	0.8 (fine) – 1.5 (coarse) mm
Feed	4500 - 8000 mm/min
Product name attribute	\varnothing 144 mm
Brush $\varnothing D_1$	144 mm
Disc dia. D_2	150 mm
Grinding media	Ceramic grit (CER)
Grinding medium code	Ceramic
Bristle length L_3	43 mm
Working area \varnothing	144 mm
Bore $\varnothing d_1$	32 with groove mm
recommended speed	1000 - 1200 rpm
maximum speed	2500 rpm
Type of product	Disc brush

Accessories

Tightening screw with internal cooling for mandrel \varnothing 32 mm

575096 32