

Garant

Wheel brushes, silicon carbide (SiC), Ø 100 mm, Grit: 120



Order data

Order number	575062 120
GTIN	4045197977809
Item class	51P

Description

Version:

Round brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life. Nylon bristles with very high **silicon carbide grit content** for general-purpose use.

With longitudinal groove for clamping on face mill arbors (DIN 6357) and combination face mill adapters (DIN 6358).

Advantage:

- **Workpiece post-processing directly after the machining process.**
- **Reproducible results due to continuous exposure of the abrasive grit.**
- **Process reliability thanks to high stability and accuracy of the shape.**
- **Quick and secure mounting without further accessories.**
- **Very high concentricity.**

Application:

On **CNC machining centres** and when used by robots, preferably **wet grinding** with cooling lubricant. **For grinding side faces and inner faces:** precise deburring (e.g. threads), edge rounding, delicate work after milling, surface finishing.

Note:

Special versions available on request.

Bore Ø d₁: 22 with groove mm

Grinding medium code: SiC

Grit designation: medium
Bristle thickness: 0.6 mm

Technical description

Grit	120
Grit designation	medium
Brush $\varnothing D_1$	100 mm
recommended speed	2400 - 2800 rpm
Bristle thickness	0.6 mm
maximum speed	4500 rpm
Infeed	0.3 (fine) – 1.0 (coarse) mm
Feed	800 - 3000 mm/rev.
Grinding media	Silicon carbide (SiC) grit
Grinding medium code	SiC
Product name attribute	\varnothing 100 mm
Bristle width L_1	20 mm
Bristle length L_3	22 mm
Bore $\varnothing d_1$	22 with groove mm
Propulsive equipment	CNC machining centres, robot applications
Adapter	Face mill arbor
Type of product	Wheel brush

Accessories

Tightening screw with internal cooling for mandrel \varnothing 22 mm

575096 22