# Garant

## Wheel brushes, silicon carbide (SiC), Ø 125 mm, Grit: 120



### Order data

Order number	575064 120
GTIN	4045197977823
Item class	51P

### Description

#### Version:

Round brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life. Nylon bristles with very high **silicon carbide grit content** for general-purpose use.

With longitudinal groove for clamping on face mill arbors (DIN 6357) and combination face mill adapters (DIN 6358).

#### Advantage:

- · Workpiece post-processing directly after the machining process.
- · Reproducible results due to continuous exposure of the abrasive grit.
- $\cdot\,$  Process reliability thanks to high stability and accuracy of the shape.
- · Quick and secure mounting without further accessories.
- · Very high concentricity.

#### **Application:**

On **CNC machining centres** and when used by robots, preferably **wet grinding** with cooling lubricant. **For grinding side faces and inner faces:** precise deburring (e.g. threads), edge rounding, delicate work after milling, surface finishing.

#### Note:

Special versions available on request. Bore  $\emptyset$  d<sub>1</sub>: 22 with groove mm Grinding medium code: SiC Grit designation: medium Bristle thickness: 0.6 mm

# **Technical description**

Brush Ø D <sub>1</sub>	125 mm
Grit	120
maximum speed	4000 rpm
Grit designation	medium
recommended speed	1800 - 2200 rpm
Bristle thickness	0.6 mm
Feed	800 - 3000 mm/rev.
Infeed	0.3 (fine) – 1.0 (coarse) mm
Grinding medium code	SiC
Grinding media	Silicon carbide (SiC) grit
Product name attribute	Ø 125 mm
Bristle width L <sub>1</sub>	20 mm
Bristle length L₃	22 mm
Bore Ø d <sub>1</sub>	22 with groove mm
Propulsive equipment	CNC machining centres, robot applications
Adapter	Face mill arbor
Type of product	Wheel brush

## Accessories

Tightening screw with internal cooling for mandrel $\varnothing$ 22	575006 22
mm	575096 22