

Garant**Wheel brushes, silicon carbide (SiC), Ø 150 mm, Grit: 120****Order data**

Order number	575066 120
GTIN	4045197977847
Item class	51P

Description**Version:**

Round brushes with **extremely tightly packed abrasive bristles (right to the edge of the brush)** embedded in the plastic pad. The bristles support each other, giving a **highly stable shape**. Very long working life. Nylon bristles with very high **silicon carbide grit content** for general-purpose use.

With longitudinal groove for clamping on face mill arbors (DIN 6357) and combination face mill adapters (DIN 6358).

Advantage:

- **Workpiece post-processing directly after the machining process.**
- **Reproducible results due to continuous exposure of the abrasive grit.**
- **Process reliability thanks to high stability and accuracy of the shape.**
- **Quick and secure mounting without further accessories.**
- **Very high concentricity.**

Application:

On **CNC machining centres** and when used by robots, preferably **wet grinding** with cooling lubricant. **For grinding side faces and inner faces:** precise deburring (e.g. threads), edge rounding, delicate work after milling, surface finishing.

Note:

Special versions available on request.

Bore Ø d₁: 32 with groove mm

Grinding medium code: SiC

Grit designation: medium
Bristle thickness: 0.6 mm

Technical description

recommended speed	1500 - 2000 rpm
Bristle thickness	0.6 mm
Grit	120
maximum speed	3500 rpm
Grit designation	medium
Brush $\varnothing D_1$	150 mm
Feed	800 - 3000 mm/rev.
Infeed	0.3 (fine) – 1.0 (coarse) mm
Grinding medium code	SiC
Grinding media	Silicon carbide (SiC) grit
Product name attribute	\varnothing 150 mm
Bristle width L_1	25 mm
Bristle length L_3	35 mm
Bore $\varnothing d_1$	32 with groove mm
Propulsive equipment	CNC machining centres, robot applications
Adapter	Face mill arbor
Type of product	Wheel brush

Accessories

Tightening screw with internal cooling for mandrel \varnothing 32 mm

575096 32