LENOX 🐴

Hole saw, bi-metal, Diameter: 210 mm



Order data

Order number	589030 210
GTIN	5706915081657
Item class	58Z

Description

Version:

Robust unbreakable construction with variable toothing on flexible special steel body (bimetal). The reinforced stiff base is equipped with thread and drive pin holes (from \emptyset 32 mm) for secure mounting on the arbor. The high quality of the HSS teeth, the teeth geometry and the tight manufacturing tolerances guarantee the best cutting performance and tool life.

- · Variable tooth pitch 4.5 / 5.5 tpi with reinforced teeth (Tough Teeth).
- · Maximum depth of cut for all sizes
40 mm.
- · Optimised coating reduces heat development.
- · SPEED SLOT® Quick removal of the drill plug by stepped recesses.

Application:

On pillar drills, lathes or hand-held power drills at the appropriate speed. For cutting circular holes from thin-walled to thick-walled material with a flat or convex workpiece surface. Suitable for all materials such as steel, **stainless steel**, brass, copper, cast iron, light metal, wood, plasterboard and plastic panels etc. Use of lubricant will give increased tool life (metals). Also highly suitable for thin sheet metal bodywork.

Recommendation:

The use of cutting oil such as No. 084205 size 0.25 extends the service life and permits more rapid progress through the material.

Note:

Arbors and hole saws are compatible with all commercially available bi-metal hole saws apart from Bosch SDS.

For hole saws for stone see No. 788000, 788040, 788050. For carbide hole saws for steel see No. 118400, 118500, 119000.

TPI: 4.5 / 5.5

recommended speed steel: 60 rpm recommended speed INOX: 30 rpm recommended speed aluminium: 85 rpm

Technical description

recommended speed aluminium	85 rpm
recommended speed steel	60 rpm
recommended speed INOX	30 rpm
Diameter	210 mm
TPI	4.5 / 5.5
Type of product	Hole saw

Accessories

Shank Type 210L	589310 210L
Centre drill HSS Type 6KT	589430 6KT
Centre drill carbide-tipped Type 6KT	589432 6KT
Shank Type 210S	589310 2105
Quick-change mounting shank Type 210S	589314 210S