

**Strato precision surface grinding wheel D×T×H (mm), 225×20×51****Order data**

Order number	590200
GTIN	9003174414025
Item class	53Y

Description**Version:**

High performance surface grinding wheels with high-porosity bonding system for reduced thermal loading and minimal dressing diamond wear.

- **Universally applicable for reciprocating grinding processes, which significantly reduces the frequency of wheel changes in daily operation.**
- **For use on all commercially available grinding machines for tool and die making and machine tool building, e.g. Jung, ABA, Blohm, Elb, Mägerle, Ziersch & Baltrusch, Geibel & Hotz, Jones & Shipman.**
- **Cooling with emulsion is necessary, ensure good lubrication, especially on long-chipping materials.**

Specially treated Aluminium Oxide for grinding **unalloyed and low alloy unhardened steels.**

Application:

For rough grinding (roughing).

Specification:

F13A46HH11V-Strato steel low alloyed.

Note:

Profile surface grinding wheels available on request.

Shape: 1

Shape: 1

Technical description

Grinding process	Surface grinding
Grinding medium code	A
Shape	1
Disc Ø D	225 mm
Disc thickness T	20 mm
Product name attribute	225×20×51
Bore Ø H	51 mm
Type of product	Flat grinding wheel