



Strato precision surface grinding wheel D×T×H (mm), 350×40×127



Order data

| | |
|--------------|---------------|
| Order number | 590520 |
| GTIN | 9003176652821 |
| Item class | 53Y |

Description

Version:

High performance surface grinding wheels with high-porosity bonding system for reduced thermal loading and minimal dressing diamond wear.

- **Universally applicable for reciprocating grinding processes, which significantly reduces the frequency of wheel changes in daily operation.**
- **For use on all commercially available grinding machines for tool and die making and machine tool building, e.g. Jung, ABA, Blohm, Elb, Mägerle, Ziersch & Baltrusch, Geibel & Hotz, Jones & Shipman.**
- **Cooling with emulsion is necessary, ensure good lubrication, especially on long-chipping materials.**

Specially treated Aluminium Oxide for grinding **unalloyed and low alloy unhardened steels.**

Application:

For rough grinding (roughing).

Specification:

F13A46HH11V-Strato steel low alloyed.

Note:

Profile surface grinding wheels available on request.

Shape: 1

Shape: 1

Technical description

| | |
|------------------------|---------------------|
| Grinding process | Surface grinding |
| Grinding medium code | A |
| Shape | 1 |
| Disc Ø D | 350 mm |
| Disc thickness T | 40 mm |
| Product name attribute | 350×40×127 |
| Bore Ø H | 127 mm |
| Type of product | Flat grinding wheel |