

# VIB STAR precision grinding wheel CBN D×T×H (mm) B126, 300×20×127, Coating thickness X: 3 mm



#### **Order data**

| Order number | 592025 3      |
|--------------|---------------|
| GTIN         | 9003173021378 |
| Item class   | 53Y           |

### **Description**

#### **Version:**

Surface grinding and external cylindrical grinding wheels, **highly developed**, with **superabrasives** (CBN or diamond) in synthetic resin bonding. The high-strength, **vibration-optimised VIB STAR grinding wheel base body** permits a **high damping** for a smooth, even grinding process with high surface quality.

- Extreme performance improvement (G-factor) compared to conventional grinding media.
- The vibration-damping design of the carrier body significantly increases the working life.
- · Continuous self-sharpening effect due to even power consumption and avoidance of cyclical sharpening operations.

CBN grit for high performance grinding of **long-chipping ferrous materials** such as hardened high-alloy chrome steels and HSS tool steels (including powder metallurgy grades) and nickel-based alloys.

#### **Application:**

- · General use for all materials from a hardness of about 58 HRC (limit of economic use).
- For surface grinding and external cylindrical grinding (straight longitudinal grinding, recess grinding).

- Can be used on all commercially available grinding machines for tool and die making and machine tool building, e.g. Jung, ABA, Blohm, Elb, Mägerle, Ziersch & Hotz, Jones & Shipman.
- · Cooling with emulsion or grinding oil is necessary.
- Superabrasive CBN / diamond grinding wheels are always used with less than half the wheel width compared to that for conventional grinding wheels.

#### **Specification:**

#### **B126C50B-VIB-STAR HSS**

#### Note:

Before initial grinding, these grinding wheels can be dressed on a soft steel block at an infeed of approx. 0.02 mm. Alternatively with a dressing tool No. 599600. Sharpen grinding wheels (opening up the bonding) using sharpening stone No. 599840.

Shape: 1A1

Abrasive coating height X: 3 mm

## **Technical description**

| Grinding process          | External cylindrical  |
|---------------------------|-----------------------|
| Grinding process          | Surface grinding      |
| Grinding media            | Cubic Boron Nitride   |
| Grinding medium code      | CBN                   |
| Specification             | B126C50B-VIB-STAR HSS |
| Shape                     | 1A1                   |
| Disc Ø D                  | 300 mm                |
| Disc thickness T          | 20 mm                 |
| Product name attribute    | 300×20×127            |
| Bore Ø H                  | 127 mm                |
| Abrasive coating width U  | 20 mm                 |
| Abrasive coating height X | 3 mm                  |
| Type of product           | Grinding wheel        |