# TROLD

VIB STAR precision grinding wheel DIAMANT D×T×H (mm) D126, 200×10×51, Coating thickness X: 3 mm



# Order data

| Order number | 592040 3      |
|--------------|---------------|
| GTIN         | 9009012027402 |
| Item class   | 53Y           |

# Description

## Version:

Surface grinding and external cylindrical grinding wheels, **highly developed**, with **superabrasives** (CBN or diamond) in synthetic resin bonding. The high-strength, **vibration-optimised VIB STAR grinding wheel base body** permits a **high damping** for a smooth, even grinding process with high surface quality.

- Extreme performance improvement (G-factor) compared to conventional grinding media.
- The vibration-damping design of the carrier body significantly increases the working life.
- Continuous self-sharpening effect due to even power consumption and avoidance of cyclical sharpening operations.

Diamond coating for high performance grinding of **short chipping non-ferrous materials** such as carbide, ceramic materials (PCS), hard coatings.

## Application:

- $\cdot$  General use for all materials from a hardness of about 58 HRC (limit of economic use).
- For surface grinding and external cylindrical grinding (straight longitudinal grinding, recess grinding).

## Data sheet

- Can be used on all commercially available grinding machines for tool and die making and machine tool building, e.g. Jung, ABA, Blohm, Elb, Mägerle, Ziersch & Hotz, Jones & Shipman.
- · Cooling with emulsion or grinding oil is necessary.
- Superabrasive CBN / diamond grinding wheels are always used with less than half the wheel width compared to that for conventional grinding wheels.

## Specification:

## D126C75B-VIB-STAR W-Carbide.

#### Note:

Before initial grinding, these grinding wheels can be dressed on a soft steel block at an infeed of approx. 0.02 mm. Alternatively with a dressing tool No. 599600. Sharpen grinding wheels (opening up the bonding) using sharpening stone No. 599840.

Shape: 1A1

Abrasive coating height X: 3 mm

# **Technical description**

| Grinding process          | External cylindrical               |
|---------------------------|------------------------------------|
| Grinding process          | Surface grinding                   |
| Grinding media            | Diamond                            |
| Grinding medium code      | D                                  |
| Specification             | D126C75B-VIB-STAR tungsten carbide |
| Shape                     | 1A1                                |
| Disc Ø D                  | 200 mm                             |
| Disc thickness T          | 10 mm                              |
| Product name attribute    | 200×10×51                          |
| Bore Ø H                  | 51 mm                              |
| Abrasive coating width U  | 10 mm                              |
| Abrasive coating height X | 3 mm                               |
| Type of product           | Grinding wheel                     |