

**Bench grinding wheel D×T×H (mm), 150×20×32, Type: NK36****Order data**

|              |               |
|--------------|---------------|
| Order number | 596200 NK36   |
| GTIN         | 9003171475746 |
| Item class   | 53Y           |

**Description****Version:**

**High-quality long-lasting bench grinder wheels** in ceramic bonding. Very low radial and axial run-out, maximum cutting speed 40 m/s. For **general use** on double-ended bench grinding machines for deburring, sharpening and resharpening tools.

**Application:**

For construction steels and low-alloy steels and also grey cast iron.

**Specification:**

**Standard aluminium oxide** grey-blue, hardness grade M.

**Supplied with:**

Reducing ring set for the indicated bores.

**Note:**

For compact deburring wheels see No. 568725 ff.

Shape: 1

Shape: 1

Grinding medium code: A

Grit designation: coarse

**Technical description**

|                               |   |
|-------------------------------|---|
| Grinding media                | Aluminium Oxide grit (A)                                |
| Grinding medium code          | A   |
| maximum circumferential speed | 40 m/s  |
| Grit designation              | coarse  |
| Grit                          | 36  |
| Specification                 | Standard aluminium oxide<br>grey-blue, hardness grade M |
| Grinding process              | Bench grinder   |
| Reducing ring inner Ø         | 25 mm   |
| Reducing ring inner Ø         | 20 mm   |
| Reducing ring inner Ø         | 16 mm   |
| Shape                         | 1   |
| Disc Ø D                      | 150 mm  |
| Disc thickness T              | 20 mm   |
| Product name attribute        | 150×20×32   |
| Bore Ø H                      | 32 mm   |
| Type of product               | Grinding wheel for off-hand grinders                    |