

**Bench grinding wheel D×T×H (mm), 200×25×51, Type: NK60****Order data**

| | |
|--------------|---------------|
| Order number | 596400 NK60 |
| GTIN | 9003177183614 |
| Item class | 53Y |

Description**Version:**

High-quality long-lasting bench grinder wheels in ceramic bonding. Very low radial and axial run-out, maximum cutting speed 40 m/s. For **general use** on double-ended bench grinding machines for deburring, sharpening and resharpening tools.

Application:

For construction steels and low-alloy steels and also grey cast iron.

Specification:

Grey-blue **standard aluminium oxide**, hardness grade M

Supplied with:

Reducing ring set for the indicated bores.

Note:

For compact deburring wheels see No. 568725 ff.

Shape: 1

Shape: 1

Grinding medium code: A

Grit designation: medium

Technical description

| | |
|-------------------------------|--|
| Grit designation | medium |
| Grit | 60 |
| Grinding medium code | A |
| maximum circumferential speed | 40 m/s |
| Specification | Grey-blue standard aluminium oxide, hardness grade M |
| Grinding media | Grey-blue Aluminium Oxide |
| Grinding process | Bench grinder |
| Reducing ring inner Ø | 32 mm |
| Shape | 1 |
| Disc Ø D | 200 mm |
| Disc thickness T | 25 mm |
| Product name attribute | 200×25×51 |
| Bore Ø H | 51 mm |
| Type of product | Grinding wheel for off-hand grinders |

Accessories

Reducing ring set for the natural bore of the grinding wheel 51 mm

596000 51