

# Cutting disc D×T×H (mm), 125×1×20



## **Order data**

| Order number | 598520        |
|--------------|---------------|
| GTIN         | 9009012820799 |
| Item class   | 53Y           |

## **Description**

#### **Version:**

Non-fabric, synthetic resin-bonded Aluminium Oxide abrasive cutting disc for all steels including HSS.

### **Application:**

- Cutting on stationary cutting grinding machines (without fabric reinforcing, i.e. not suitable for free-hand cutting).
- · Working speed 30 m/s, maximum 80 m/s.

### **Specification:**

A60N5B68 HSS.

#### Note:

Saw sharpening discs available on request.

Shape: 41N Shape: 41N

## **Technical description**

| Grinding process | Cutting |
|------------------|---------|
|------------------|---------|

| Grinding media                    | Aluminium oxide, unwoven synthetic resin bonded |
|-----------------------------------|-------------------------------------------------|
| Grinding medium code              | A                                               |
| Specification                     | A60N5B68 HSS                                    |
| Shape                             | 41N                                             |
| Disc Ø D                          | 125 mm                                          |
| Disc thickness T                  | 1 mm                                            |
| Product name attribute            | 125×1×20                                        |
| Bore Ø H                          | 20 mm                                           |
| recommended circumferential speed | 30 - 50 m/s                                     |
| Type of product                   | Cutting-off wheel                               |