



Combination spanner, Width across flats: 3,2 mm



Order data

Order number	613500 3,2
GTIN	4018754019083
Item class	63A

Description

Version:

Drop-forged. With close tolerance jaw width.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS-Drive** profile. (Sizes 3.2 – 5 with hexagon).

Standard:

DIN 3113 A / ISO 3318 / ISO 7738

Material:

Chrome alloy steel, non-flaking chrome-plated over nickel; smoothed finish.

Note:

AS-Drive – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. Tools with this profile can be recognised by the **AS-Drive** symbol.

Advantage:

- **Bolts are gripped on the flanks. – The bolts are protected. – Longer bolt life.**
- **Larger contact surfaces between bolt and tool. – Secure grip and higher torque transmission.**

Spanner length L: 75 mm

maximum jaw height h₁: 3 mm

maximum ring height h_{2max}: 3.2 mm

Technical description

Spanner length L	75 mm
maximum jaw height h ₁	3 mm
Width across flats	3.2 mm
Width across flats	metric

maximum ring height $h_{2\max}$	3.2 mm
Standard	DIN 3113 A
Standard	ISO 3318
Standard	ISO 7738
Ring setting	15 degrees
Manufacturing process	drop forged
Material	Chrome alloy steel
Surface	chromium-plated over nickel
Type of product	Spanner

Accessories

Electronics tool kit, 118 pieces with aluminium tool case	680400
Electronics tool kit, 118 pieces without case	680405