



Combination spanner, imperial, Width across flats: 1/4 inches



Order data

Order number	613520 1/4
GTIN	4018754020096
Item class	63A

Description

Version:

Drop-forged. With close tolerance jaw width.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS-Drive** profile. (Sizes 3.2 – 5 with hexagon).

Standard:

DIN 3113 A / ISO 3318 / ISO 7738

Material:

Chrome alloy steel, non-flaking chrome-plated over nickel; smoothed finish.

Note:

AS-Drive – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. Tools with this profile can be recognised by the **AS-Drive** symbol. **Advantages:**

- **Bolts are gripped on the flanks. – The bolts are protected. – Longer bolt life.**
- **Larger contact surfaces between bolt and tool. – Secure grip and higher torque transmission.**

Advantage:

- **Bolts are gripped on the flanks. – The bolts are protected. – Longer bolt life.**
- **Larger contact surfaces between bolt and tool. – Secure grip and higher torque transmission.**

Spanner length L: 105 mm

maximum jaw height h₁: 4 mm

maximum ring height h_{2 max}: 6 mm

Technical description

Spanner length L	105 mm
Width across flats	1/4 inch

maximum jaw height h ₁	4 mm
Width across flats	imperial
maximum ring height h _{2 max}	6 mm
Ring setting	15 degrees
Type of product	Spanner

Accessories

Combination spanner set Number of keys 13ZOLL	613960 13ZOLL
---	---------------