



## Combination spanner, imperial, Width across flats: 15/64 inches



### Order data

Order number	613520 15/64
GTIN	2050001019271
Item class	63A

### Description

#### Version:

Drop-forged. With close tolerance jaw width.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS-Drive** profile. (Sizes 3.2 – 5 with hexagon).

#### Standard:

**DIN 3113 A / ISO 3318 / ISO 7738**

#### Material:

Chrome alloy steel, non-flaking chrome-plated over nickel; smoothed finish.

#### Note:

**AS-Drive** – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. Tools with this profile can be recognised by the **AS-Drive** symbol. **Advantages:**

- **Bolts are gripped on the flanks. – The bolts are protected. – Longer bolt life.**
- **Larger contact surfaces between bolt and tool. – Secure grip and higher torque transmission.**

#### Advantage:

- **Bolts are gripped on the flanks. – The bolts are protected. – Longer bolt life.**
- **Larger contact surfaces between bolt and tool. – Secure grip and higher torque transmission.**

Spanner length L: 95 mm

maximum jaw height h<sub>1</sub>: 3 mm

maximum ring height h<sub>2 max</sub>: 3.2 mm

### Technical description

maximum jaw height h <sub>1</sub>	3 mm
Width across flats	15/64 inch

Spanner length L	95 mm
Width across flats	imperial
maximum ring height $h_{2\max}$	3.2 mm
Ring setting	15 degrees
Type of product	Spanner