∕ystahlwillet⊖

Combination spanner, imperial, Width across flats: 7/16 inches



Order data

Order number	613520 7/16
GTIN	4018754020140
Item class	63A

Description

Version:

Drop-forged. With close tolerance jaw width.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS-Drive** profile. (Sizes 3.2 – 5 with hexagon).

Standard:

DIN 3113 A / ISO 3318 / ISO 7738

Material:

Chrome alloy steel, non-flaking chrome-plated over nickel; smoothed finish.

Note:

AS-Drive – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. Tools with this profile can be recognised by the **AS-Drive** symbol. **Advantages:**

- · Bolts are gripped on the flanks. The bolts are protected. Longer bolt life.
- Larger contact surfaces between bolt and tool. Secure grip and higher torque transmission.

Advantage:

- · Bolts are gripped on the flanks. The bolts are protected. Longer bolt life.
- Larger contact surfaces between bolt and tool. Secure grip and higher torque transmission.

Spanner length L: 135 mm maximum jaw height h1: 5.5 mm maximum ring height h_{2 max}: 10 mm

Technical description

maximum jaw height h1	5.5 mm
Width across flats	7/16 inch

Spanner length L	135 mm
Width across flats	imperial
maximum ring height h _{2 max}	10 mm
Ring setting	15 degrees
Type of product	Spanner

Accessories

Combination spanner set Number of keys 13ZOLL

613960 13ZOLL