

**Double-ended ring spanner, deeply cranked, Width across flats: 16X17 mm****Order data**

Order number	615000 16X17
GTIN	4018754020942
Item class	63A

Description**Version:**

Drop-forged. With close tolerance jaw widths.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS drive** profile.

Advantage:

AS drive profile:

- **Bolts are gripped on the flanks.**
- **The corners are protected.**
- **Longer bolt life.**
- **Larger contact surfaces between bolt and tool.**
- **Secure grip and higher torque transmission.**

Standard:

DIN 838 / ISO 3318

Material:

Chrome vanadium steel, chrome-plated.

Note:

AS-Drive – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. All GARANT and STAHLWILLE deep cranked double-ended ring spanners are equipped with this profile – recognisable by the **AS drive** mark.

Spanner length L: 255 mm

maximum ring Ø D₁ max: 25 mm

maximum ring Ø D₂ max: 27 mm

Technical description

maximum ring Ø D ₂ max	27 mm
-----------------------------------	-------

Width across flats 1	16 mm
maximum ring Ø D ₁ max	25 mm
Spanner length L	255 mm
Width across flats 2	17 mm
Width across flats	metric
Type of product	Spanner