

**Double-ended ring spanner, deeply cranked, Width across flats: 18X19 mm****Order data**

Order number	615000 18X19
GTIN	4018754020973
Item class	63A

**Description****Version:**

Drop-forged. With close tolerance jaw widths.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS drive** profile.

**Advantage:**

**AS drive** profile:

- **Bolts are gripped on the flanks.**
- **The corners are protected.**
- **Longer bolt life.**
- **Larger contact surfaces between bolt and tool.**
- **Secure grip and higher torque transmission.**

**Standard:**

**DIN 838 / ISO 3318**

**Material:**

Chrome vanadium steel, chrome-plated.

**Note:**

**AS-Drive** – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. All GARANT and STAHLWILLE deep cranked double-ended ring spanners are equipped with this profile – recognisable by the **AS drive** mark.

Spanner length L: 275 mm

maximum ring Ø D<sub>1</sub> max: 28 mm

maximum ring Ø D<sub>2</sub> max: 29 mm

**Technical description**

Width across flats 2	19 mm
----------------------	-------

maximum ring Ø D <sub>1</sub> max	28 mm
Spanner length L	275 mm
maximum ring Ø D <sub>2</sub> max	29 mm
Width across flats 1	18 mm
Width across flats	metric
Type of product	Spanner