



## Double-ended ring spanner, deeply cranked, Width across flats: 36X41 mm



### Order data

Order number	615000 36X41
GTIN	4018754021185
Item class	63A

### Description

#### Version:

Drop-forged. With close tolerance jaw widths.

With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Ring end with **AS drive** profile.

#### Advantage:

**AS drive** profile:

- **Bolts are gripped on the flanks.**
- **The corners are protected.**
- **Longer bolt life.**
- **Larger contact surfaces between bolt and tool.**
- **Secure grip and higher torque transmission.**

#### Standard:

**DIN 838 / ISO 3318**

#### Material:

Chrome vanadium steel, chrome-plated.

#### Note:

**AS-Drive** – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. All GARANT and STAHLWILLE deep cranked double-ended ring spanners are equipped with this profile – recognisable by the **AS drive** mark.

Spanner length L: 440 mm

maximum ring  $\varnothing D_1$  max: 53 mm

maximum ring  $\varnothing D_2$  max: 60 mm

### Technical description

Width across flats 1	36 mm
----------------------	-------

Width across flats 2	41 mm
maximum ring $\varnothing D_2$ max	60 mm
maximum ring $\varnothing D_1$ max	53 mm
Spanner length L	440 mm
Width across flats	metric
Type of product	Spanner