



## Double-ended ring spanner, shallow cranked, Width across flats: 8X9 mm



### Order data

Order number	616500 8X9
GTIN	4018754021666
Item class	63A

### Description

#### Version:

Drop-forged. With close tolerance jaw widths. Thin, flat rings for use in restricted places. With easy-grip fluted shaft. Optimum flexional resistance, good torque transmission. Shallow cranked head at each end. With **AS Drive** profile.

#### Standard:

**DIN 897 / ISO 3318**

#### Material:

Chrome alloy steel, non-flaking chrome-plated over nickel; smoothed finish.

Spanner length L: 179 mm

maximum ring  $\varnothing D_1$  max: 12.1 mm

maximum ring  $\varnothing D_2$  max: 13.3 mm

maximum ring height  $h_{1\max}$ : 8 mm

### Technical description

maximum ring $\varnothing D_1$ max	12.1 mm
Width across flats 2	9 mm
Spanner length L	179 mm
maximum ring height $h_{1\max}$	8 mm
Width across flats 1	8 mm
maximum ring $\varnothing D_2$ max	13.3 mm
Width across flats	metric
Manufacturing process	drop forged

Material	Chrome alloy steel
Surface	chromium-plated over nickel
Type of product	Spanner

---

## Accessories

Double-ended ring spanner set, shallow cranked Number of keys 8	616510 8
--	----------