



## Double-ended open ring spanner, Width across flats: 14X17 mm



### Order data

Order number	619200 14X17
GTIN	4018754015344
Item class	63A

### Description

#### Version:

Drop forged; with reinforced ring, therefore exceptionally strong; jaw widths to exact tolerances. 10° angled heads.

With easy-grip fluted shaft. Optimum flexural strength, good torque transmission, very light and easy to use. Up to size 12×14 mm with hexagon ring - size 14×17 mm and above with bi-hexagon.

#### Standard:

**DIN 3118 / ISO 3318**

#### Material:

Chrome alloy steel; non-flaking, chrome-plated over nickel.

Spanner length L: 200 mm

maximum ring  $\varnothing D_1$  max: 26 mm

maximum ring  $\varnothing D_2$  max: 30 mm

maximum ring height  $h_{1\max}$ : 10.5 mm

maximum ring height  $h_{2\max}$ : 12 mm

### Technical description

maximum ring height $h_{1\max}$	10.5 mm
maximum ring $\varnothing D_1$ max	26 mm
maximum ring $\varnothing D_2$ max	30 mm
Spanner length L	200 mm
maximum ring height $h_{2\max}$	12 mm
Width across flats 2	17 mm

Width across flats 1	14 mm
Width across flats	metric
Standard	DIN 3118 / ISO 3318
Ring setting	10 degrees
Manufacturing process	drop forged
Material	Chrome alloy steel
Surface	chrome-plated (non-flaking)
open ring	yes
Type of product	Spanner