

Bi-hexagon socket, 1/2 inch, Width across flats: 34 mm



Order data

| Order number | 642100 34 |
|--------------|---------------|
| GTIN | 4018754005413 |
| Item class | 63A |

Description

Version:

Forged from high quality steel, internally bevelled for easy fitting to bolt heads. Close tolerance internal square for secure fit on the tool. Square socket drives to **DIN 3120.**

Optimum grain orientation due to special forging process. Close tolerance width across flats. No rounding of bolt corners, nuts and bolt heads are protected. Hardened in an oil bath, stress-relieved and distortion-free for a precision fit. Smoothed finish. **AS drive** profile.

Standard:

DIN 3124

Material:

HPQ® high performance steel, non-flaking chrome-plated over nickel.

Square drive: 1/2 inch

 \varnothing drive output end: 45 mm

Length: 47 mm

Technical description

| Ø drive output end | 45 mm |
|--------------------|----------|
| Width across flats | 34 mm |
| Length | 47 mm |
| Square drive | 1/2 inch |

| Standard | DIN 3124 |
|------------------------|-----------------------------|
| Drive profile | Bi-hex socket |
| Material | HPQ® high performance steel |
| Surface | chromium-plated over nickel |
| with AS Drive profile. | yes |
| Type of product | Socket insert |