

Koken

IMPACT hexagon socket, 1/2 inch thin-walled, with plastic sleeve, Width across flats: 19 mm



Order data

Order number	651240 19
GTIN	4991644359424
Item class	63R

Description

Version:

Sturdy shape especially for use with electric or compressed air impact wrenches. With cross hole and snap ring groove for securing sockets. Internal square to DIN 3121.

For safety reasons must always be secured using a suitable locking pin and O-ring.

Advantage:

- **Smaller Ø and perfectly matched overall length of the socket permits working on bolts where access is difficult.**
- **Protective sleeve prevents damage to delicate components (such as aluminium rims).**
- **Can be positioned while the wrench is running, because the protective sleeve is free-running.**
- **Inserts are quickly distinguished colour code.**
- **The torsion zone permits the socket to accept high loadings.**

Application:

Especially for avoiding damage to delicate components (such as alloy wheel rims) during assembly.

Standard:

DIN 3129

Material:

Chrome molybdenum steel, surface burnished.

Note:

For spare protective sleeves see No. 651242

Square drive: 1/2 inch

Ø drive output end: 27.2 mm

Length: 110 mm

Technical description

Ø drive output end	27.2 mm
Length	110 mm
Width across flats	19 mm
Square drive	1/2 inch
Drive profile	Hexagon socket
Type of product	Socket insert

Accessories

Retainer clip set, 10 pieces, for sockets, 1/2 inch, including extractor Type 3	651790 3
Locking pin for sockets, 1/2 inch Ø×Length 3X20 mm	651900 3X20
“O” ring for sockets, 1/2 inch Ø 25 mm	651800 25
Plastic protective sleeve Type 19	651242 19