



Electronic torque screwdriver tester "TST", maximum torque: 10 Nm



Order data

Order number	654300 10
GTIN	2050001016935
Item class	66D

Description

Version:

- **Robust polyurethane body for table mounting or wall hanging.**
- **Large-format LCD display.**
- **Direct choice from the test procedure pictogram keypad for**
- **Interface for connection to an external sensor. When using sensors No. 654350 the measurement range and the calibration parameters are recognised automatically.**
- **Frequency displays for checking pulsed tools or screwdrivers with slip couplings.**
- **Target torque values with upper and lower tolerance limits can be programmed.**
- **Serial interface for connection to a printer or PC.**
- **Power supply: Integral rechargeable battery for approx. 16 hours free-standing use, or 230V mains operation.**
- **TCS calibration software (available free of charge after registration at www.norbar.com/en-gb/downloads/torque-certification-system).**

Integral sensor with 1/4 inch hexagon C 6.3 and additional connection for 1 external sensor.

Advantage:

Flexible measuring system can be extended to 100,000 Nm. Very easy to use.

Application:

Calibrating torque screwdrivers with adjustment scale or display. Setting and calibrating torque screwdrivers without scale. **Setting and calibrating electric or pneumatic screwdrivers** with automatic shut-off. Use optional external measurement transducers to calibrate torque wrenches or torque screwdrivers up to 100,000 Nm.

Supplied with:

Supplied with UKAS calibration certificate, right-hand and screw tightening simulator for calibrating electric or pneumatic screwdrivers, 2 fastening screws, serial data transmission cable in a plastic case.

Note:

Screw tightening simulators for No. 654300 and 654350 under No. 654352.

Not suitable for impact wrenches.

Calibration: O4

Torque measuring accuracy: $\pm 0.5\%$

Measuring range: 0.5 - 10 Nm

Display unit width: 288 mm

Display unit height: 72 mm

Display unit depth: 160 mm

Weight: 2.2 kg

Technical description

Measuring range	0.5 - 10 Nm
Weight	2.2 kg
Display unit width	288 mm
Display unit depth	160 mm
maximum torque	10 Nm
Display unit height	72 mm
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081560 CR2032
Torque measuring accuracy	$\pm 0.5\%$
Power supply	Battery-powered
Direction of tightening	Right-hand tightening
Interface	RS232C interface
Test certificate	Manufacturer's test certificate
Calibration	O4
Type of product	Torque screwdriver

Services

DAkKS calibration Torque analyser / sensor maximum torque 1000/2 Nm

018840 1000/2

Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
DAkkS calibration Torque analyser / sensor maximum torque 1000 Nm	018840 1000
Labelling laser-etched Type	018940
Calibration, right Torque analyser / sensor Type 400	020120 400
DAkkS calibration, right Torque analyser / sensor Type 1000	020130 1000
DAkkS calibration on both sides Torque analyser / sensor maximum torque 1000/2 Nm	020150 1000/2

Accessories

Flange mounted transducer "FMT" maximum torque 2 Nm	654350 2
Software for monitoring torque wrenches	654270
Flange mounted transducer "FMT" maximum torque 150 Nm	654350 150
Flange mounted transducer "FMT" maximum torque 400 Nm	654350 400
Screw tightening simulator maximum torque 10 Nm	654352 10
RS232 PC connection cable	654344
Flange mounted transducer "FMT" maximum torque 1500 Nm	654350 1500
Flange mounted transducer "FMT" maximum torque 10 Nm	654350 10
Flange mounted transducer "FMT" maximum torque 25 Nm	654350 25